

Maximum Flexibility at an Exceptional Price!

Introducing the *Express Tag 6000*, Unimark's newest travel industry printer. The state-of-the-art design of the *Express Tag 6000* is founded on a 32 bit microprocessor and multi-level dot history control of the printhead to produce crisp text, bar codes, and graphics at speeds up to 8 inches per second. The self centering paper path provides maximum flexibility when printing baggage tags, cargo labels, or ATB coupons.

The Express Tag 6000, the Clear Choice!

Features of the *Express Tag 6000* include:

- Affordability and Reliability
- RFID Enabled
- Multi-Purpose Printer: Baggage Tags, Boarding Passes and Cargo Labels
- Produces 25 Baggage Tags per Minute
- Produces 60 ATB Coupons per Minute
- Auto-Loading and Top-of-Form Sensing



SPECIFICATIONS

Print Technology

- Direct thermal printing
- Print speed up to 8 ips (203 mmps)
- 203 dpi (8dpmm) print resolution
- Intelligent printhead - multi level dot history control to maximize print speed and extend printhead life
- Dot-out detection and reporting

Print Modes

- Large number of standard text fonts available
- Custom text fonts available upon request
- Full graphics capability
- Bar code printing in one and two dimensional symbols
- Prints text, bar codes, and graphics in all four directions

Documents

- Accepts fan-fold or roll baggage tag stock
- Accepts boarding pass ATB coupons
- Accepts fan-fold or roll cargo labels
- Self centering paper path
- Auto-loading and top-of-form sensing
- Handles stock lengths up to 25" (635 mm) and stock widths up to 3.62" (92 mm)

Electronics

- 32 Bit microprocessor
- Supports program download
- NV-RAM supporting PECTAB, logo, font, and template downloads
- 2x20 character backlit LCD display
- Eight key control panel for system access
- Four LED status display

Communications Interface

- RS232C serial port
- Supports baud rates up to 38.4 kbps
- Optional Ethernet LAN interface supporting TCP/IP, Telnet, DHCP, DNS, ARP, BOOTP, FTP, UDP, SMTP, SNMP, and HTTP
- Custom communication interfaces available: (LAN, parallel port, serial port, etc.)

Options

- Cutter
- RFID Module
- External Stacker
- Roll Stock Configuration
- Integrated Ethernet Interface
- RF Bridge to 802.11 Compliant Wireless Network

Physical Characteristics

- Width = 8.625 inches (219 mm)
- Height = 6.5 inches (165 mm)
- Depth = 16.75 inches (425 mm)
- Weight = 15 pounds (6.78 kg)
- Operating Temperature Range: 40°F to 104°F, 4°C to 40°C

Power

- 100-120/200-240 VAC, 50/60 Hz auto ranging and switching



Specifications Subject to Change

Corporate Headquarters

Unimark Inc.
9910 Widmer
Lenexa, KS 66215
United States
Ph (800) 255-6356
(913) 649-2424
FAX (913) 649-5795

North American Service Center

Unimark Service
9910 Widmer
Lenexa, KS 66215
United States
Ph (800) 451-2926
(913) 649-2424
FAX (913) 649-3483

European Sales & Service

Unimark Europe Ltd.
Woodlands Business Park - Unit 3
Woodlands Park Avenue
Maidenhead, Berkshire
England
Ph +44-1628-829-990
FAX +44-1628-829-991

Internet

Address www.unimark.com
E-Mail solutions@unimark.com