



Less Size, Less Cost, More Value.

Introducing the *Sprite*, Unimark's newest travel industry printer. The *Sprite* is a state-of-the-art design combining superior functionality, flexibility and reliability at an affordable price. The space-saving design, ease-of-use and optional configurations make the *Sprite* the perfect choice for travel agency and airport locations.

Features of the *Sprite* include:

- Affordability
- Reliability
- 10 Coupons per Minute Printing
- Dual Stock Inputs
- Space-Saving Design
- Optional STP Configuration



Unimark

The Partner of Choice!

S P E C I F I C A T I O N S

Print Technology

- Direct-Thermal
- 203dpi (8dppm) print resolution
- Full graphics capability
- Processes up to 10 documents per minute

Documents

- Issues ATB1 or ATB2 coupons
- Fan-folded, continuous feed stock with burst separation from two separate bins
- Two rear feed, external stock paths

Operational Mode Options

- AEA
- Line Printer Emulation
- Satellite Ticket Printer (STP) with internal modem
- Custom host interfaces available

Magnetics Option

- Encoding to IATA RP 1722 and Resolution 722
- Fully ATB2 compliant
- Four tracks - read, write, and write verification (210 bpi)
- Magnetic SCN read

Communications Interface Options

- Dual RS232 serial, 300-19,200 BPS, 25 pin (F)
- Combined serial and centronics parallel
- Combined modem and serial
- Direct network attachment
- Custom communication interfaces available



STP Configuration with Optional Secured Media Cabinet

Additional Options

- Lockable Stock Bin with 1000 coupon capacity configurable as two 500 coupon internal stacks or as one 1000 coupon internal stack with one 1000 coupon external stack
- Lockable Exit Door
- NV-RAM for PECTAB and logo storage
- Flash Memory for diskless operation

Physical Characteristics

- Width = 9 inches (229 mm)
- Height = 15 inches (381 mm)
- Depth = 9 inches (229 mm)
- Depth with Lock Box = 22 inches (559 mm)
- Weight = 18 pounds (8.2 kg)

Power

- 115 / 220 VAC (+/- 10%) auto-sensing
- 50/60 Hz

Compliance

- Fully compliant with IATA ATB2 specifications
- Compliant with ATA Resolutions
- CE Compliant
- FCC Class A, UL 1950, ISO EN6950, CSA 22.2, No. 950-M89

Specifications Subject to Change

Corporate Headquarters

Unimark Inc.
9910 Widmer
Lenexa, KS 66215
United States
Ph (800) 255-6356
(913) 649-2424
FAX (913) 649-5795

North American Service Center

Unimark Service
9910 Widmer
Lenexa, KS 66215
United States
Ph (800) 451-2926
(913) 649-2424
FAX (913) 649-3483

European Sales & Service

Unimark Europe Ltd.
Woodlands Business Park - Unit 3
Woodlands Park Avenue
Maidenhead, Berkshire
England
Ph +44-1628-829-990
FAX +44-1628-829-991

Internet

Address www.unimark.com
E-Mail atbcserv@unimark.com