

Faster
More Reliable
Quieter



Creating a New Standard in ATB Performance!

Introducing the Unimark **XP**, the transportation industry's most advanced ATB printer. Powered by dual 32 bit microprocessors, the **XP** goes where no other ATB printer has dared to go: On a Diet! The **XP** has 50% fewer components and is 20 pounds lighter than its predecessor, the MARK I. The **XP** leverages the proven document handling design with leading edge electronics to deliver a Fast, Lightweight, Quiet, User Friendly, and Reliable ATB printer. The Unimark **XP** is the clear choice for travel agencies, airports, and satellite ticket printing applications.

Features of the Unimark **XP** include:

- ▶ **Fast, Quiet, Rugged and Reliable**
- ▶ **Processes 50 Documents per Minute**
- ▶ **Three Autoloading Ticket Bins**
- ▶ **Internal Ethernet Interface with Integrated Web Browser Technology**
- ▶ **Easy to Use and Maintain**



S P E C I F I C A T I O N S

Print Technology

- Direct Thermal, 203dpi (8dpmm) Print Resolution
- Intelligent Thermal Printhead Technology
- Print Speed up to 8 ips (203 mm/ps)
- Print Line Width 3.15" (80 mm)
- Full Graphics Capability
- Contains Andale from Agfa Monotype Corporation
- Optional Character Fonts and Bar Codes
- Processes 50 Documents per Minute

Documents

- Issues ATB1 or ATB2 Documents
- Three Auto-Loading Input Bins
- Fan-Folded, Continuous Feed Stock with Burst Separation from Three Separate Bins
- Accepts 8" (203 mm) and 7 3/8" (187 mm) Stocks
- Front Feed Revalidation Path

Magnetics, Optional

- Encoding to IATA RP 1722 and Resolution 722
- Fully ATB2 compliant
- Four tracks - read, write, and write verification (210 bpi)
- SCN pre-read prior to bursting
- Internal void bin

Electronics and User Interface

- Dual 32 Bit Microprocessors
- EPROM: 2 MB
- RAM: 3 MB
- NVRAM: 1 MB
- 2x20 Character Backlit LCD Display
- Eight Button User Keypad
- Four Status LED's

Communications Interface

- Dual RS232 Serial Ports
- Optional Integrated LAN Interface
- Optional Parallel Port
- Optional USB Port
- Optional Internal Modem
- Supports all Popular ATB Interfaces Including AEA Specifications

Physical Characteristics

- Width = 11 5/8 inches (295 mm)
- Height = 23 1/2 inches (597 mm) (w/o casters)
- Depth = 21 3/4 inches (552 mm)
- Weight = 50 pounds (22.7 kg)

Power

- 115 / 220 VAC (+/- 10%) Auto-Sensing
- 50/60 Hz

Environment

- Operating Temperature 40F to 104F (4C to 40C)
- Storage Temperature -4F to 140F (-20C to 60C)

Compliance

- Fully Compliant with IATA ATB2 Specifications
- Compliant with ATA Resolutions
- FCC, UL, CE, CSA, and TUV

Options

- Memory Expansion: EPROM, RAM and NVRAM
- Smart Card Module
- Communication Interfaces: Parallel, USB and Integrated LAN
- STP Model with Internal Modem
- Bin C Locking Stock Box
- Large Capacity Stacker
- Bin C Shelf

Specifications Subject to Change

Corporate Headquarters

Unimark Inc.
9910 Widmer
Lenexa, KS 66215
United States
Ph (800) 255-6356
(913) 649-2424
FAX (913) 649-5795

North American Service Center

Unimark Service
9910 Widmer
Lenexa, KS 66215
United States
Ph (800) 451-2926
(913) 649-2424

European Sales & Service

Unimark Europe Ltd.
Woodlands Business Park - Unit 3
Woodlands Park Avenue
Maidenhead, Berkshire
England
Ph +44-1628-829-990
FAX +44-1628-829-991

Internet

Address www.unimark.com
E-Mail solutions@unimark.com